



Produced By:

ULTRA PURE DIESEL EXHAUST FLUID

ULTRA PURE LIQUIDE D'ÉCHAPPEMENT DIESEL

ULTRA PURE DE FLUIDO DE ESCAPE DIESEL

Safety:

Handling information: Ensure good ventilation at the workplace. Avoid prolonged or repeated skin contact. Avoid contact with eyes. Material Safety Data Sheet containing detailed information about this product is available on request.

Handling and Storage :

The shelf life of DEF is directly related to the temperature at which it is stored.

Storage temperature between 12° and 86° F are recommended to maintain optimal shelf life of up to two years. If DEF freezes, its efficacy will not be effected upon thawing.

To maintain the purity of DEF and not harm the SCR Catalyst System care must be taken regarding the material of construction for all items that come in contact with the DEF solution.

DO'S AND DON'TS FOR PROPER USE OF DEF

- Do fill DEF in designated DEF Tank
- Do keep DEF dispense equipment clean, and free from dust or dirt
- Do use only dedicated DEF equipment when handling/dispensing DEF
- Do not fill DEF into Diesel fuel tank
- Do not fill Diesel fuel into DEF tank
- Do not add water to DEF

Marketing and Distribution: KING Additives LLC 3701 Junius # D009 Dallas, Texas 75246
www.kingadditives.com US: www.kingdef.com EU: www.kingadblue.com

DEF ISO 22241

CAUTION: May cause skin and eye irritation

PRECAUCIÓN: Puede causar irritación de la piel y de los ojos

ATTENTION: Peut causer une irritation de la peau et des yeux

Approved in use of all diesel SCR emission reduction systems

Approuvé lors de l'utilisation de tous les systèmes de réduction des émissions diesel SCR

Aprobado en el uso de todos los sistemas de reducción de emisiones diesel SCR



VDA OMC